

PRODUCT DESCRIPTION

- Basic cover dedicated to most standard KLUS extrusions of small size
- Good light diffusion


Fill empty fields

Product nr.	
Fixture type	
Company	
Job name	
Date	

TECHNICAL SPECIFICATION

Material	PC
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	no

TECHNICAL DRAWING







RELATED PROFILES



OPK-4 Profile Ref: C0370







OLEK Profile Ref: B8505



PDS-4-K Profile Ref: B3776



45-ALU Profile Ref: B4023



DES Profile Ref: 18030



NISA-KRA Profile Ref: 18026





PDS-ZM Profile Ref: B7696



GLAD-45 Profile Ref: B7009



POLI Profile Ref: B7176



NISA-NI Profile Ref: 18029



PDS-H Profile Ref: B9204




Ref: B3775

POR Profile


Ref: B6144



45-16 Profile Ref: B8504



PDS-4-ALU Profile Ref: B1718



PDS-O Profile Ref: B3777



KOZMA Profile Ref: 18040



NISA-KON Profile Ref: 18027



Ref: 18035





NISA-PLA Profile Ref: 18028



STEP Profile

Ref: 18042





PULA Profile













OBIT Profile Ref: W4826



E Profile PAG





PAC-MDF Profile Ref: 0972





PDS-4-PLUS Profile Ref: C1263



STOS-MDF Profile

PDS-ZMG Profile Ref: C1418



MICRO-HG Profile Ref: C1419

MOD-50 Profile Ref: 18047

MICRO-NK Profile Ref: C1587

MOD-100 Profile Ref: 18049