



PRODUCT DESCRIPTION

The cover has a matt black surface that turns white when the light is turned on, the line of light at 160LED/m. The cover material is PC (polycarbonate) with increased resistance to UV radiation. The best visual effect is obtained with profiles that are black inside. The cover creates a line of light in profiles minimal deep 11 mm at 160LED/1m.

- They blend in with dark lighting fixtures and dark surfaces of ceilings or walls
- A surprising light effect when the light is switched on

Fill empty fields

Product nr.	
Fixture type	
Company	
Job name	
Date	



TECHNICAL SPECIFICATION

Application


- decorative lighting

Assembly

- snap-in in dedicated profiles

Material	PC
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	increased

TECHNICAL DRAWING





RELATED PROFILES



OPK-4 Profile Ref: C0370





MICRO-H Profile Ref: C0599

Ref: B1888

PDS-ZM Profile

Ref: B7696



OLEK Profile Ref: B8505



PDS-4-K Profile Ref: B3776



45-ALU Profile Ref: B4023



DES Profile Ref: 18030



NISA-KRA Profile Ref: 18026




GLAD-45 Profile

Ref: B7009

NISA-NI Profile Ref: 18029



PDS-H Profile Ref: B9204



MICRO-ALU Profile MICRO-K Profile Ref: B3775





PDS-4-ALU Profile Ref: B1718



PDS-O Profile Ref: B3777



KOZMA Profile Ref: 18040




NISA-KON Profile Ref: 18027



Profile Ref: C1263





















KUBIK-45 Profile Ref: B7697







Ref: C1418



MICRO-HG Profile Ref: C1419



MOD-50 Profile Ref: 18047



MICRO-NK Profile Ref: C1587



RELATED PRODUCTS

MARKETING MATERIALS





Display P230-90154M Ref: 90154M

