

PRODUCT DESCRIPTION

- Line of light
- Concealed aluminum elements
- The profile does not interfere with a structure made of 5/8 inch (about 16mm) thick drywall

FINISH:

Non anodized (raw)	
--------------------	--



Fill empty fields

Product nr.	
Fixture type	
Company	
Job name	
Date	

TECHNICAL SPECIFICATION

Application

- to create a line of light flush with the surface of walls and ceilings

Assembly

- fixed in the groove with mounting adhesive
- profile fastening wings covered with gypsum plaster
- The PROTECTIVE INSERT TECH-50 ensures that the profile slot remains wide enough for the snap-in cover (its use is NECESSARY during mounting and finishing works)

Additional information

- designed for up to four 10 mm wide LED strips
- line of light obtainable with the LIGER-50 cover and LED strips with a minimum of 120 LED /m
- the cover is evenly illuminated with four LED strips, with fewer strips shadows appear on the cover
- the KOZUS-50 profile is equipped with ZM sockets. ZM Connectors are used to connect profiles lengthwise. They are easily accessible even after mounting the profile in the ceiling
- the groove cut out in the drywall to accommodate the profile should be 51mm 56mm wide


AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
C0958NA_1	Non anodized (raw)	1000 mm
C0958NA_2	Non anodized (raw)	2000 mm



Ref. nr.	surface finish	available lengths
C0958NA_3	Non anodized (raw)	3000 mm

TECHNICAL DRAWING





RELATED PRODUCTS

COVERS



Ref: 17086

END CAPS



Ref: 24282

ACCESSORIES



COUPLERS - CONNECTION METHODS FOR PROFILES














L90PZ T135L







More accessories on our page www.klusdesign.eu